

# DHI-PHMIA135-CF

## COB Foldable All-In-One LED



### Technical Specification

#### Model

Model	DHI-PHMIA135-CF
-------	-----------------

#### Parameters

Pixel Pitch	1.56mm
Pixel Configuration	1R1G1B
LED Type	Flip COB 3 In 1
Brightness (Max)	≥600 nit
Viewing Angle (H/V°)	160°/160°
Pixel Density	409,600 dot/m <sup>2</sup>
Module Size	150mm×168.75mm
Display Resolution(W×H)	1920×1080
Visible Area (H x V)	3000mm×1687.5mm
Overall Size (W×H×D)	3014mm×2630mm×770mm(Rise to the top) 1804mm×1980mm×770mm(Folding down)
Weight	513kg(Include flight case)
Display Size	135-inch
Cabinet Material	Die-cast aluminum
IP Rating	Front IP30/Rear IP30
Operating Temperature/ Humidity	-10 C~+40 C /20%~70%RH
Storage Temperature/ Humidity	-10 C~+50 C /20%~80%RH

### Features :

- Fully flip COB module, bumping and moisture-proof;
- Folded inward screen, and the collision sensing system is built into the electric lifting bracket to effectively prevent the screen body from bumping;
- Ready to use without installation;
- Wireless screen projection, file push, reverse control screen, code sharing, brightness sensing;
- Flip camera and fingerprint unlock to ensure privacy.



Gray Scale	13bits
Contrast Ratio	10000:1
Refresh Rate	3840 Hz
Input Voltage	AC100~240V
Input Power (Max)	2400W
Input Power (Avg)	800W
Installation Mode	Free installation with lifting and moving bracket
Maintenance Mode	Front Maintenance
System / Storage Memory	8G / 64G
Control Interface	RJ45x1,USB 3.0x4,Bluetoothx1,WIFI6x1,Light perceptionx1,Infrared remote controlx1
Video Interface	HDMIx2 (1 in 1 out),TYPE-C x1
Audio Interface	Built-in 4x15W speakers,3.5mm Line Out x1
System	Android 11/Windows 11 (Optional)
Standard Accessories	Remote Control Vacuum Front Maintenance Tool
WiFi Standard	WiFi STATION: 802.11b/g/n/a/ac/ax WiFi AP: 802.11b/g/n/a/ac
WiFi Frequency Range	WiFi STATION: 2400-2483.5MHz, 5150-5250MHz, 5250-5350MHz, 5470-5725MHz, 5725-5850MHz WiFi AP: 2400-2483.5MHz,5150-5350MHz
WiFi MAX Transmission Power	≤20dBm@2400-2483.5MHz;≤23dBm@5150-5250MHz; ≤20dBm@5250-5350MHz;≤27dBm@5470-5725MHz; ≤14dBm@5725-5850MHz
Bluetooth Standard	BR/EDR/BLE(Bluetooth mode), BT5.0(Bluetooth version)
Bluetooth Frequency Range	2400-2483.5MHz
Bluetooth MAX Transmission Power	≤20dBm@2400-2483.5MHz

# DHI-PHMIA135-CF

COB Foldable All-In-One LED

